

Neutralisation NB

Neutralisation system for floor-standing gas and oil condensing units up to 4000 kW

The NB neutraliser cleans and neutralises the condensate from gas and oil condensing units so that it does not destroy the sewage system and subsequently the environment. Thanks to the integrated condensate siphon, the NB can be installed quickly. The NB neutraliser is available with and without a feed pump.















Neutralisation NB for gas heaters

Products Gas	Perfor- mance heaters	integr. Air- pump	Height inlet / outlet	Dimensions (with / without Pump)	Article number
NB 1.0	up to 200 kW	no	125 mm / 105 mm 125 mm / Pump	L: 350 mm W: 350 / 230 mm H: 180 mm	1001210 (without Pump) 1001215 (with Pump)
NB 1.1	up to 500 kW	no	125 mm / 105 mm 125 mm / Pump	L: 350 mm W: 350 / 230 mm H: 180 mm	1001211 (without Pump) 1001216 (with Pump)
NB 2.0	up to 1000 kW	no	115 mm / 95 mm 115 mm / Pump	L: 600 / 460 mm W: 310 mm H: 270 / 180 mm	1001212 (without Pump) 1001217 (with Pump)
NB 3.0	up to 2000 kW	no	110 mm / 95 mm 110 mm / Pump	L: 800 / 665 mm W: 410 mm H: 270 /185 mm	1001213 (without Pump) 1001218 (with Pump)
NB 4.0	up to 4000 kW	no	145 mm / 120 mm 145 mm / Pump	L: 1000 / 860 mm W: 615 mm H: 270 / 240 mm	1001214 (without Pump) 1001219 (with Pump)

Neutralisation NB for Oil heaters

Products Oil	Perfor- mance heaters	integr. Air- pump	Height inlet / outlet	Dimensions (with / without Pump)	Article number
NB 1.0	up to 100 kW	no	125 mm / 105 mm 125 mm / Pump	L: 350 mm W: 350 / 230 mm H: 180 mm	1001210 (without Pump) 1001215 (with Pump)
NB 1.1	up to 250 kW	no	125 mm / 105 mm 125 mm / Pump	L: 350 mm W: 350 / 230 mm H: 180 mm	1001211 (without Pump) 1001216 (with Pump)
NB 2.0	up to 500 kW	no	115 mm / 95 mm 115 mm / Pump	L: 600 / 460 mm W: 310 mm H: 270 / 180 mm	1001212 (without Pump) 1001217 (with Pump)
NB 3.0	up to 1000 kW	no	120 mm / 95 mm 120 mm / Pump	L: 800 / 665 mm W: 410 mm H: 270 / 185 mm	1001213 (without Pump) 1001218 (with Pump)
NB 4.0	up to 2000 kW	no	145 mm / 120 mm 145 mm / Pump	L: 1000 / 860 mm W: 615 mm H: 270 / 240 mm	1001214 (without Pump) 1001219 (with Pump)



Your benefits with Neutralisation NB at a glance

• Plug & Play:

The NB neutralisation unit can be combined with all gas and oil condensing units plug & play. It is available with and without feed pump.

• Legal requirements:

The NB neutralisation unit is equipped with an integrated condensate siphon in accordance with the specifications of the Association of Cantonal Fire Insurers (VKF).

• Additional connection:

If required, the condensate from the flue gas system can also be connected.